



Specifications

Housing

20-gauge (.0359) CRS formed, sheet metal construction. Finished in low glare, polyester mineral bronze powder coat.

Reflector

24-gauge (.020) formed aluminum substrate with a silver-based polyester film laminate. 95% specular reflectance.

Barn Door

Hinged to the bottom front of the fixture face. Pivots down to 90°. Swings up to protect fixture face when unit is not in use.

Ballasts

(6) Digital high-frequency electronic ballast for 28W to 54W (High Output option). 120 or 230VAC, 50/60Hz, power factor =>.97, class "A" sound rating, THD<10%. The ballasts allow dimming down to 3% without flashing or flickering. DMX Master Unit required for DMX to Digital protocol conversion.

Lamps

(12) 28W or 54W (HO option), available in red, green, and blue. Red, green, and blue colored sleeves are provided with 28W lamps for more saturated colors.

Lamp Sockets

G5, 2-pin twist-and-lock molded white high-strength thermoplastic.

Power Entry Module

IEC-320 connector with integral 8-amp fuse and holder for spare fuse.

DMX Master Unit

DMX in and out receptacles and digital ballast output receptacle. The DMX start address can be set anywhere between 1 and 512; the fixture uses three consecutive DMX addresses. The DMX output is self-terminating; no termination switch is required. Unit is capable of driving up to 9 remote units.

Remote Unit

Digital ballast input and output receptacles. Unit must be driven by a DMX master unit. Remote units are daisy-chained together.

Mounting Bracket

10-gauge extruded aluminum yoke for horizontal or vertical mounting. Horizontal yoke standard; add "-V" to part number for vertical yoke.

Power Cord

12' (3.66 m) length 18/3 gauge SOW cable 10amp/250V. Female IEC connector to male grounded 3-pin Edison plug (NEMA 5-15P). Black color. Optional connectors available upon request.

Electrical Certification

cUL, CE, and C-Tick listed.

Includes

Fixture comes standard with four each red, green, and blue 28W or 54W lamps, color sleeves with 28W lamps; horizontal or vertical yoke; a power cord, and C-clamp with safety cable.

