

## Double-Dome-Mount Videoconference Fixture

### Construction

Fixture housing is made of formed, cold-rolled sheet steel. Dome-shaped interior fixture housing. Perforated filler panels are optional.

### Fixture Body Finish

Low-gloss, off-white finish (Tiger Drylac #44911704) is standard, with custom colors available.

### Fixture Carriage and Reflector

Two sizes of lamp carriages are available, housing one or two 55-W lamps. Reflectors are of formed-aluminum specular-sheet-metal construction, featuring 95% reflectance. Direct/indirect task lights are available to provide for soft, glare-free room illumination. Wall Washer housing (one lamp) provided with reflective white finish.

### Ballast

Ballasts are available in switched or in a variety of dimmable configurations. All ballasts are high-frequency electronic, with a Power Factor > .97, THD < 10%, and a Class A sound rating. Ballasts are housed in the fixture housing. Power and control inputs are from the side.

### Lamps

All Brightline fixtures use 55-W compact fluorescent lamps, available in a variety of color temperatures and CRI ratings (see the Fixture Accessories and Lamps datasheet for details). Studioline and Cinema Series lamps are optimized specifically for video camera applications.

Shipping Information
Length: 28 in (711 mm)
Width: 25.5 in (648 mm)
Height: 14.5 in (368 mm)
Weight: 60 lb (27.2 kg)

### Articulation

Rotate: Fixture carriage mounted on a sliding bracket allows for greater range of angular movement (+/- 50 degrees) on a single axis.

Drop-Pan-Tilt: Provides three axes of movement. DPT fixture carriages move up and down from the ceiling, revolve 360 degrees, and rotate angularly (+/- 70 degrees).

Motorized: Fixtures with motorized articulation are available in a configuration featuring a two-lamp carriage. Offers angular movement (+/- 50 degrees) on a single axis.

### Accessories

A variety of control screens are available to shape the light-beam pattern (see the Fixture Accessory and Lamps datasheet for details). White-finish screens are standard, with black finish as an option. Prismatic lenses are available for one- and two-lamp carriages.

### Fixture Dimensions

Inch Panel: 23.750 x 23.750 x 7.072 in  
(603.25 x 603.25 x 179.62 mm)

Metric Panel: 595 x 595 x 179.62 mm  
(23.43 x 23.43 x 7.072 in)

Fixture Weight: 44 lb (16 kg)

### Electrical Certifications


UL, cUL, CE, and C-Tick




Fixture shown with One-Lamp Rotate and Two-Lamp Drop carriage.

US Patent No. 6,517,216. Other US and foreign patents pending.


**Sample Fixture Configurations**




One-One-Lamp Rotate with left slide and Two-Lamp Rotate with maximum left slide (includes contrast light).




Two-Lamp Rotate with maximum right slide and with contrast light, and Two-Lamp Drop-Pan-Tilt (shown in dropped position and tilted).




Two One-One Rotate with slide to achieve maximum outward rotation (includes contrast light).




Two-Lamp Rotate with maximum left slide and Task Light showing perforated diffusion screen.



Two-Lamp Rotate in centered position and One-Lamp Rotate with maximum left (includes contrast light).



Wall Washer showing lamp and indirect reflector and Two-Lamp Rotate with maximum left slide (includes contrast light).



Two-Lamp Rotate with maximum right slide and with contrast light, and One-Lamp Drop-Pan-Tilt (shown in dropped position and tilted).

<b>T</b>				
<b>T-Series</b>	Lamp Carriage	Lamp Carriage	Ballast Type	Voltage
	01= One 1-Lamp Carriage	01= One 1-Lamp Carriage	E = Ecosystem	1 = 120v
	11= Two 1-Lamp Carriages	11= Two 1-Lamp Carriages	N = Non-Dim	2= 230v
	02= One 2-Lamp Carriage	02= One 2-Lamp Carriage	P = Phase	7 = 277v
	OR	OR	X = DALI	
	00= No Lamp Carriage	00= No Lamp Carriage		

Articulation	Articulation
R = Rotate & Contrast	R = Rotate & Contrast
D = Drop-Pan-Tilt	D = Drop-Pan-Tilt
M = Motorized Rotate	M = Motorized Rotate
OR	OR
T = Task	T = Task
W = Wall Wash	W = Wall Wash

Panel Size	Panel Style	Mounting Style
I = Inch	S = Solid	DD = Double Dome
M = Metric	P = Perforated	

Note: EcoSystem Ballasts have a THD of 20%.

Note: Phase-Dim ballasts are not available in 230V.

Note: Custom Finish is available. Add a "-CF" to the end of the part number.

Note: Fixtures require Control Screens and Lamps; see Fixture Accessories and Lamps datasheet for options.